

# TX-3011-03-1

## 2 button panic 868 MHz Gen2, white

---

The sensor is a supervised, wireless hold-up or panic device and can be worn around the neck using the strap provided. The sensor contains two activation buttons. An alarm is activated by pressing and holding both buttons for a minimum of half a second. The led on the sensor flashes for one minute following the alarm activation. The sensor is water resistant.



### Details

---

- Learn-mode technology
- 2 button activation
- Supervised
- Worn around neck using the strap
- LED to confirm alarm activation

# TX-3011-03-1

## 2 button panic 868 MHz Gen2, white

### Technical specifications

---

#### General

Type	Pendant
Water resistant	No

#### Wired / wireless

Wired / wireless	Wireless
Wireless frequency	868 MHz AM
Open-air range	150 m

#### Electrical

Batteries	1 x 3 V lithium battery
Battery lifetime	3 years

#### Physical

Physical dimensions	64 x 46 x 13 mm
Colour	White

#### Compatible with

Interlogix 868 MHz Gen2 receivers
-----------------------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2023 - 9:33